



# Icron USB 3-2-1 Starling™ 3251C Series

## 1-Port USB 3.2 Gen 1 Type-C 10m Extender System

### Short-Distance USB 3-2-1 Extension Solutions

The Icron USB 3-2-1 Starling 3251C Series provides short-distance extension with all USB 3.2 Gen 1 (5Gbps), USB 2.0/1.1 device types across a point-to-point connection. Bus-powered, the 3251C is available with either a custom fixed length CM or Plenum-Rated cable.



4664 Lougheed Hwy.  
Suite 221  
Burnaby, BC,  
V5C 5T5, Canada

www.icron.com  
+1 604 638 3920

#### Product Contents

- USB 3-2-1 Starling 3251C LEX
- USB 3-2-1 Starling 3251C REX
- USB 3.2 Gen 1 USB-C Cable (USB only)
- 10m Link Cable\* (CM or Plenum-Rated)
- Cable Pulling Eye Tool
- Quick Start Guide



Specifications subject to change  
without notification.

©2023

Icron | An Analog Devices Brand

#90-01829-D03



LEX



REX



10m Custom Link Cable with  
included Cable Pulling Eye Tool

### Summary of Features


- USB 3.2 Gen 1 data rate up to 5Gbps
- Supports all USB 3.2 Gen 1, 2.0, 1.1 devices simultaneously at full bandwidth
- USB-C port connectivity (USB data only)
- Bus-powered with optional DC input
- Single custom 10-meter CM or Plenum-Rated Link Cable with included Cable Pulling Eye Tool
- FCC and CE (Class A) compliant

#### Includes the ExtremeUSB-C™ suite of features:

- Transparent USB extension supporting USB 3, 2 and 1
- True plug and play; no software drivers required
- Works with all major operating systems: Windows®, macOS™, Linux® and Chrome OS™







### Applications

- Remote Storage
- Security and Monitoring
- Conference Rooms
- Test and Measurement



# Icron USB 3-2-1 Starling 3251C Series Specifications



LEX (LOCAL EXTENDER) MECHANICALS	REX (REMOTE EXTENDER) MECHANICALS	CUSTOM LINK CABLE
1x USB 3.2 Gen 1 Type-C Receptacle	1x USB 3.2 Gen 1 Type-C Receptacle	10m CM or Plenum-Rated Active Copper Cable
1x ARJ45 Link Port (For included cable only)	1x ARJ45 Link Port (For included cable only)	Bend Radius: 35mm (1.4")
5V 3A DC Jack (Power supply sold separately)	86.0 x 45.0 x 24.0mm (3.4" x 1.8" x 0.9")	Conduit Diameter (min): 19mm (3/4")
86.0 x 45.0 x 24.0mm (3.4" x 1.8" x 0.9")	Silver Anodized Aluminum	ARJ45 Connector Width: 13mm (0.5")
Silver Anodized Aluminum		
		 Cable Pulling Eye Tool Width: 18mm (0.7")
		 ARJ45 Connector Width: 13mm (0.5")

RANGE	
Point-to-Point:	10 meters (32.8 feet)
USB SUPPORT	
USB Speeds:	SuperSpeed 5Gbps, High-Speed, Full-Speed, Low-Speed
USB Bandwidth:	Up to 5Gbps
Device Compatibility:	All Device Types and Classes (Control, Interrupt, Isochronous and Bulk)
Available Current at REX:	Up to 900mA
Max Number of USB Devices:	30, including hubs
ENVIRONMENTAL	
Temperature:	Operating: 0°C – 50°C (32°F – 122°F), Storage: -20°C – 70°C (-4°F – 158°F)
Humidity:	Operating 20-80%, Storage 10-90% Relative Humidity Non-Condensing
COMPLIANCE	
Certifications	FCC (Class A), CE (Class A), RoHS2/3 (CE), ICES-003 Issue 7, EN 62368-1
SUPPORT	
Warranty:	2 years

## Ordering Information

The Icron USB 3-2-1 Starling 3251C system includes a LEX, REX, USB 3.2 Gen 1 USB-C Cable (USB only), 10m Link Cable\* (CM or Plenum-Rated depending on the model), Cable Pulling Eye Tool, Quick Start Guide and two-year warranty. To order or for more information, please contact us at [www.icron.com/contact](http://www.icron.com/contact) or call +1 604 638 3920.

PART #	NAME	DESCRIPTION
00-00456	Icron USB 3-2-1 Starling 3251C-10	1-Port USB 3-2-1 Type-C 10m Extender, CM Cable
00-00457	Icron USB 3-2-1 Starling 3251C-10-PL	1-Port USB 3-2-1 Type-C 10m Extender, Plenum Cable
00-00459	Icron USB 3-2-1 Starling 3251C-10-NC*	1-Port Icron USB 3-2-1 Starling 3251C-10, No CM Cable
00-00464	Icron USB 3-2-1 Starling 3251C-10-PL-NC*	1-Port Icron USB 3-2-1 Starling 3251C-10-PL, No Plenum-rated Cable
21-00159	10m CM Link Cable only	Packaged 10m CM Link Cable
21-00160	10m Plenum Link Cable only	Packaged 10m Plenum Link Cable
21-00111	5V 3A Power Adapter (Level VI) 1.7mm ID	AC Desktop Adapter, 5V 3A, Lvl6, Intl, 1.7mm (ID) plug, IEC320-C7/C8 2-pin
21-00115	NA Ungrounded Power Cord	Cable Power IEC320-C7/C8 1.83m 2-pin NA
21-00116	EU Ungrounded Power Cord	Cable Power IEC320-C7/C8 1.83m 2-pin EU
21-00117	UK Ungrounded Power Cord	Cable Power IEC320-C7/C8 1.83m 2-pin UK
21-00118	AU Ungrounded Power Cord	Cable Power IEC320-C7/C8 1.83m 2-pin AU
21-00109	JP Ungrounded Power Cord	Cable Power IEC320-C7/C8 1.5m 2-pin JP
21-00155	Starling Silver USB Mounting Kit	USB Mounting Kit (Starling) Silver - 4 Brackets

\*00-00459 and 00-00464 SKUs must use 21-00159 or 21-00160 (respectively) to function.