

USB 2.0 Ranger® 2211

1-Port USB 2.0 100m Cat 5e Extender System with Flexible Power

The USB 2.0 Ranger® 2211 extends high-speed USB 2.0 connections up to 100m using Cat 5e* with the option to power either the LEX (Local Extender) or REX (Remote Extender).



4664 Lougheed Hwy.
Suite 221
Burnaby, BC,
V5C 5T5, Canada

www.icron.com
sales@icron.com
+1 604 638 3920



LEX



REX

Features

The Ranger 2211 is ideal for extending USB peripherals including: keyboards, mice, interactive whiteboards, flash drives, hard drives, audio devices, web cameras and any other USB device.

- Flexible power — connect the power adapter to either the LEX or REX
- Supplies 500mA to USB devices
- Utilizes Cat 5e cable for convenient installation
- Supports throughputs of up to 480 Mbps


Includes the ExtremeUSB® suite of features:

- Transparent USB extension
- Plug and play; no software drivers required
- Works with all major operating systems: Windows®, OS X® and Linux®

Applications

- Interactive white board
- Keyboard and mouse extension
- Sensor/data acquisition
- Industrial control

←EXTREME
USB®



Specifications subject to
change without notification.
©2015
Icron Technologies Corp.
#90-00949-A05

* This product supports Cat 5e or better cabling (i.e. Cat 6, Cat 7, etc.). All references to "Cat 5e" should be read as "Cat 5e or better".

USB 2.0 Ranger® 2211 Specifications



Specifications subject to change
without notification.
©2015
Icron Technologies Corp.
#90-00949-A05



RANGE

Direct Connect: Up to 100m (330 ft) over Cat 5e (or better)

SPEEDS

USB 2.0: Up to 480 Mbps

USB 1.1: Up to 12 Mbps

POWER

Power Supply: 100-240V AC Input, 24V DC Output

LEX

USB Connector: 1 x USB Type B Receptacle

Link Connector: 1 x RJ45

Dimensions: 85mm x 57mm x 28mm (3.35" x 2.25" x 1.10")

Mounting: Slots for Cable Ties

Enclosure Material: Black ABS with Rubberized Coating

REX

USB Connector: 1 x USB Type A Receptacle

Link Connector: 1 x RJ45

Available Current: 500mA

Dimensions: 85mm x 57mm x 28mm (3.35" x 2.25" x 1.10")

Mounting: Slots for Cable Ties

Enclosure Material: Black ABS with Rubberized Coating

ENVIRONMENTAL

Operating Temperature: 0°C to 50°C (32°F to 122°F)

Storage Temperature: -20°C to 70°C (-4°F to 158°F)

Operating Humidity: 20% to 80% relative humidity, non-condensing

Storage Humidity: 10% to 90% relative humidity, non-condensing

COMPLIANCE

EMC: FCC (Class A), CE (Class A)

Immunity: CE Criteria A

Environmental: RoHS2 (CE)

Safety: Flammability V-0

SUPPORT

Warranty: 2-year

Ordering Information

The USB 2.0 Ranger® 2211 system includes a LEX, REX, USB Cable, Quick Start Guide, international power adapter with country specific power cord and two-year warranty. For more information, email sales@icron.com or call +1 604 638 3920.

PART #	NAME	DESCRIPTION
00-00315	USB 2.0 Ranger® 2211 - NA	1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, NA Power Cord
00-00316	USB 2.0 Ranger® 2211 - EU	1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, EU Power Cord
00-00317	USB 2.0 Ranger® 2211 - UK	1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, UK Power Cord
00-00318	USB 2.0 Ranger® 2211 - AU	1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, AU Power Cord
00-00369	USB 2.0 Ranger® 2211 - JP	1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, JP Power Cord