

# USB 2.0 RG2311 Extender

1-Port USB 2.0 100m CAT 5e/6/7 Extender System with Flexible Power

The USB 2.0 RG2311 extends high-speed USB 2.0 connections up to 100m using CAT 5e/6/7 with the option to power either the Local Extender or Remote Extender.



## Features

The RG2311 is ideal for extending USB peripherals including: keyboards, mice, interactive whiteboards, flash drives, hard drives, audio devices, web cameras and any other USB device.


- Flexible power — connect the power adapter to either the Local or Remote Extender
- Supplies up to 1 Amp to USB port
- Mass Storage Acceleration for USB 2.0 device bulk transfers
- Supports throughputs of up to 480 Mbps

Includes the ExtremeUSB® suite of features:

- Transparent USB extension
- Plug and play; no software drivers required
- Works with all major operating systems: Windows®, macOS™ and Linux®

## Applications

- Interactive white board
- Keyboard and mouse extension
- Sensor/data acquisition
- Industrial control



4664 Lougheed Hwy.  
Suite 221  
Burnaby, BC,  
V5C 5T5, Canada

www.icron.com  
+1 604 638-3920

EXTREME  
USB®

Specifications subject to  
change without notification.  
©2016  
Icron Technologies Corp.  
#90-01441-A01

# USB 2.0 RG2311 Specifications

## RANGE

Direct Connect: Up to 100m (330 ft) over CAT 5e/6/7

## SPEEDS

USB 2.0: Up to 480 Mbps

USB 1.1: Up to 12 Mbps

## POWER

Power Supply: 100-240V AC Input, 24V 1A DC Output

## LOCAL EXTENDER

USB Connector: 1 x USB Type B Receptacle

Link Connector: 1 x RJ45

Dimensions: 65.0mm x 87.5mm x 30.0mm (2.6" x 3.4" x 1.2")

Mounting: Slots for Cable Ties

Enclosure Material: Black ABS with Rubberized Coating

## REMOTE EXTENDER

USB Connector: 1 x USB Type A Receptacle

Link Connector: 1 x RJ45

Available Current: Up to 1 Amp to USB port

Dimensions: 65.0mm x 87.5mm x 30.0mm (2.6" x 3.4" x 1.2")

Mounting: Slots for Cable Ties

Enclosure Material: Black ABS with Rubberized Coating

## ENVIRONMENTAL

Operating Temperature: 0°C to 50°C (32°F to 122°F)

Storage Temperature: -20°C to 70°C (-4°F to 158°F)

Operating Humidity: 20% to 80% relative humidity, non-condensing

Storage Humidity: 10% to 90% relative humidity, non-condensing

## COMPLIANCE

EMC: FCC (Class A), CE (Class A)

Environmental: RoHS2 (CE)

Safety: Flammability V-0

## SUPPORT

Warranty: 2-year



## Ordering Information

The USB 2.0 RG2311 system includes a Local Extender, Remote Extender, USB Cable, Quick Start Guide, one international power adapter with country specific power cord and two-year warranty. For more information, email [sales@icron.com](mailto:sales@icron.com) or call +1 604 638 3920.

PART #	NAME	DESCRIPTION
01-00580	USB 2.0 RG2311 - NA	1-Port USB 2.0 Flexible Power CAT 5e/6/7 100m Extender System, 100-240V Power Adapter, NA Power Cord
01-00581	USB 2.0 RG2311 - EU	1-Port USB 2.0 Flexible Power CAT 5e/6/7 100m Extender System, 100-240V Power Adapter, EU Power Cord
01-00582	USB 2.0 RG2311 - UK	1-Port USB 2.0 Flexible Power CAT 5e/6/7 100m Extender System, 100-240V Power Adapter, UK Power Cord
01-00583	USB 2.0 RG2311 - AU	1-Port USB 2.0 Flexible Power CAT 5e/6/7 100m Extender System, 100-240V Power Adapter, AU Power Cord
01-00584	USB 2.0 RG2311 - JP	1-Port USB 2.0 Flexible Power CAT 5e/6/7 100m Extender System, 100-240V Power Adapter, JP Power Cord