

www.icron.com +1 604 638 3920

Specifications subject to change without notification. Icron | An Analog Devices Brand

Icron USB 3-2-1 Raven[™] 3104 Pro

4-Port USB 3.2, 100m CAT 6a/7 Point-to-Point Extender System

USB 3-2-1 Extender over Category Cable Optimized for Camera and Video Capture Devices

The Icron USB 3-2-1 Raven 3104 Pro provides the ability to connect all USB 3.2 Gen 1 (5Gbps) device types and is backwards compatible to USB 2.0 and 1.1 across a point-to-point connection up to 100m over CAT 6a/7. The Raven 3104 Pro also includes an Ethernet pass-through for connecting to network enabled devices or to use existing infrastructure without losing LAN connectivity.



Summary of Features

- USB 3.2 Gen 1 data rate up to 5Gbps
- Supports all USB 3.2 Gen 1, 2.0, 1.1 devices simultaneously at full bandwidth
- Four available 3.2 Gen 1 ports
- 100/1000 Ethernet channel; LAN pass-through
- Single cable, CAT 6a/7 up to 100m
- Point-to-point connection
- Supports all USB transfer types (Control, Interrupt, Isochronous and Bulk)
- Optimized for camera and video capture devices
- FCC and CE (Class B) compliant

Includes the ExtremeUSB-C[™] suite of features:

- Transparent USB extension supporting USB 3, 2 and 1
- True plug and play; no software drivers required
- Works with all major operating systems: Windows®, macOS™, Linux® and Chrome OS™

Applications

- Remote Storage
- Video Matrix Systems
- Security and Monitoring
- **Conferencing Cameras**



#90-01740-D01

Icron USB 3-2-1 Raven 3104 Pro Specifications

LEX (LOCAL EXTENDER) MECHANICAL DATA	REX (REMOTE EXTENDER) MECHANICAL DATA
137.3 x 232.1 x 33.0mm (5.4" x 9.1" x 1.3")	137.3 x 232.1 x 33.0mm (5.4" x 9.1" x 1.3")
1x USB 3 Type B Receptacle	4x USB 3 Type A Receptacles
1x RJ45 Ethernet 100/1000 Port	1x RJ45 Ethernet 100/1000 Port
1x RJ45 Ethernet Link Port	1x RJ45 Ethernet Link Port
24V 1A DC Locking Jack	24V 2.71A DC Locking Jack
Silver Anodized Aluminum	Silver Anodized Aluminum
920g (2.03 lbs.)	990g (2.18 lbs.)
PACKAGE CONTENTS	
1x LEX (Local Extender)	
1x REX (Remote Extender)	←EXTREME
1x USB 3.2 Gen 1 Cable	USB □ C
2x International Locking AC Adapters	USDC
2x Country Specific Power Cords	
1x Quick Start Guide	

RANGE	ANGE		
Point-to-Point:	Up to 100m over CAT 6a/7		

USB SUPPORT	
USB Speeds:	SuperSpeed 5 Gbps, High-Speed, Full-Speed, Low-Speed
USB Bandwidth:	Up to 5Gbps
Device Compatibility:	All Device Types and Classes (Control, Interrupt, Isochronous and Bulk)
Host Compatibility:	OHCI, UHCI, EHCI, xHCI
Available Current at REX:	1.2A (6W) per USB port
Max Number of USB Devices:	30

ENVIRONMENTAL	
Temperature:	0°C – 50°C (32°F – 122°F) Operating, -20°C – 70°C (-4°F – 158°F) Storage
Humidity:	20-80% Operating, 10-90% Storage Relative Humidity Non-Condensing
COMPLIANCE	

COMPLIANCE	
Certifications:	FCC (Class B), CE (Class B), RoHS2/3 (CE), ICES-003 Issue 7, EN 62368-1
SUPPORT	
Warranty:	2 years

Ordering Information

The Icron USB 3-2-1 Raven[™] 3104 Pro system includes a LEX, REX, USB 3.2 Gen 1 cable, two international power adapters with country specific power cords, Quick Start Guide and two-year warranty. To order or for more information, contact us at www.icron.com/contact or call +1 604 638 3920.

PART #	NAME	DESCRIPTION
00-00451	Icron USB 3-2-1 Raven 3104 Pro - NA	Icron 4-Port Pro USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - NA
00-00452	Icron USB 3-2-1 Raven 3104 Pro - EU	Icron 4-Port Pro USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - EU
00-00453	Icron USB 3-2-1 Raven 3104 Pro - UK	Icron 4-Port Pro USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - UK
00-00454	Icron USB 3-2-1 Raven 3104 Pro - AU	Icron 4-Port Pro USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - AU
00-00455	Icron USB 3-2-1 Raven 3104 Pro - JP	Icron 4-Port Pro USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - JP
10-00620	Raven Silver Mounting Kit	Raven/Maverick Silver Mounting Kit, Set of 2 Mounting Brackets, Bolts included