

USB 2.0 RG2211 Extender

1-port USB 2.0 100m Cat 5e Extender System with Flexible Power

Sold as unbranded or private label

The RG2211 extends high-speed USB 2.0 connections up to 100m using Cat 5e* with the option to power either the local extender or remote extender.



Local Extender



Remote Extender

Features

The RG2211 is ideal for extending USB peripherals including: keyboards, mice, interactive whiteboards, flash drives, hard drives, audio devices, web cameras and any other USB device. Key features include:


- Flexible power—connect the power adapter to either the local or remote extender
- Supplies 500mA to USB devices
- Utilizes Cat 5e cable for convenient installation
- Supports throughputs of up to 480Mbps
- Reliable operation with USB 2.0 and 1.1 devices and hubs

Includes the ExtremeUSB® suite of features:

- Transparent USB extension
- True plug and play; no software drivers required
- Works with all major operating systems: Windows®, Mac OS X®, and Linux®

Applications

- Interactive white board
- Keyboard and mouse extension
- Sensor/data acquisition
- Industrial control



* This product supports Cat 5e or better cabling (i.e. Cat 6, Cat 7, etc). All references to "Cat 5e" should be read as "Cat 5e or better".

USB 2.0 RG2211 Specifications

RANGE

Direct Connect: 100m (330 ft) over Cat 5e (or better)

SPEEDS

USB 2.0: Up to 480Mbps

USB 1.1: Up to 12Mbps

POWER

Power Supply: 100-240V AC Input, 24V DC Output

LOCAL EXTENDER

USB Connector: 1 x USB Type B Receptacle

Link Connector: 1 x RJ45

Dimensions: 85mm x 57mm x 28mm (3.35" x 2.25" x 1.10")

Mounting: Slots for Cable Ties

Enclosure Material: Black ABS with Rubberized Coating

REMOTE EXTENDER

USB Connector: 1 x USB Type A Receptacle

Link Connector: 1 x RJ45

Available Current: 500mA

Dimensions: 85mm x 57mm x 28mm (3.35" x 2.25" x 1.10")

Mounting: Slots for Cable Ties

Enclosure Material: Black ABS with Rubberized Coating

ENVIRONMENTAL

Operating Temperature: 0°C to 50°C (32°F to 122°F)

Storage Temperature: -20°C to 70°C (-4°F to 158°F)

Operating Humidity: 20% to 80% relative humidity, non-condensing

Storage Humidity: 10% to 90% relative humidity, non-condensing

COMPLIANCE

EMC: FCC (Class A), CE (Class A)

Immunity: CE Criteria A

Environmental: RoHS2 (CE)

Safety: Flammability V-0

SUPPORT

Warranty: 2-year



Specifications subject to change
without notification.
©2014
Icron Technologies Corp.
#90-00950-A10

Ordering Information

The USB 2.0 RG2211 system includes a local extender, remote extender, USB cable, Quick Start Guide, international power adapter with country specific power cord and 2-year warranty. For more information email sales@icron.com or call +1 604 638 3920.

PART #	NAME	DESCRIPTION
01-00382	RG2211 - NA	Unbranded 1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, NA Power Cord
01-00383	RG2211 - EU	Unbranded 1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, EU Power Cord
01-00384	RG2211 - UK	Unbranded 1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, UK Power Cord
01-00385	RG2211 - AU	Unbranded 1-Port Flexible Power Cat 5e 100m Extender System, 100-240V Power Adapter, AU Power Cord